GASCOMIN Mineral Oil USP

White mineral oil, a lubricant and protective oil for household and industrial use. For wood food-preparation surfaces, food-processing machines, rust prevention on knives and stainless steel care.

BENEFITS

- Lubricates food-processing machines
- Protects wood food-preparation surfaces
- Helps prevent rust on knives; for stainless steel care
- Ready to use as supplied



USES

Where to use

- Food-processing plants
- Commercial and household kitchens

DIRECTIONS

1. Use as supplied; do not dilute.
2. Not for internal use: do not swallow and do not use as a laxative.
3. Avoid contact with eyes. Ventilate where mist is produced, such as by spraying, heating or high-speed machinery.
4. Keep away from heat, sparks and open flames. Wipe up spills promptly: spilled oil makes floors slippery.
5. Do not transfer to unlabeled containers or to containers for food or drink. Keep out of reach of children.

AVAILABLE PACKAGES

Code	Package	UPC
D13012	Case of 4 jugs, 4 x 1 US gal (3.785 L)	787302130122
D13014	Pail, 5 US gal (18.93 L)	787302130146
D13016	Drum, 55 US gal (208.2 L)	787302130160

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid (oily)	**Color**	Clear, colorless
Odor	Odorless when cold; faint petroleum odor when heated	**pH**	Not applicable (non-aqueous liquid)
Relative density (water = 1)	0.833 to 0.861 at 25 °C (77 °F)	**Flash point**	Greater than 112 °C (234 °F), closed cup; approx. 199 °C (391 °F), Cleveland open cup
Flammability	Combustible liquid; not classified as a flammable liquid (flash point greater than 93 °C (200 °F))	**Solubility in water**	Insoluble

SAFETY

DANGER

May be fatal if swallowed and enters airways.



Hazard ratings



Health	2
Flammability	0
Physical hazard	0

NFPA 704 and HMIS ratings: 0 minimal, 1 slight, 2 moderate, 3 serious, 4 severe.

Personal protection	**Eyes and face:** Safety glasses with side shields. Wear chemical splash goggles where splashing is possible, such as when pouring or transferring the product. **Hands:** Oil-resistant gloves, such as nitrile rubber, for prolonged or repeated contact. Confirm breakthrough time with the glove manufacturer for the conditions of use.
Storage	Store in the original container, tightly closed, in a cool, dry, well-ventilated area, away from heat, sparks, open flames and direct sunlight. Store locked up and out of the reach of children. Keep away from strong oxidizing agents. Store in accordance with NFPA 30 (Class IIIB combustible liquid) and local fire codes.
Emergency	Poison Control: 1-800-222-1222 (24 hours)

Make sure your employees read and understand the Safety Data Sheet (SDS) and the product label before use. Safety values on this sheet are taken from SDS-D13012 version 2 (2026-10-25). SDSs in English and Spanish are available at www.gascoindustrial.com, from your sales representative or at (787) 737-4000.

Gascó Industrial Corp.
PO Box 1360, Gurabo, PR 00778
(787) 737-4000 · orders@gascoindustrial.com · www.gascoindustrial.com

For more information call (787) 737-4000 or visit www.gascoindustrial.com.