ECO CLEAN · TECHNICAL DATA SHEET

Laundry Bleach 12%

Sodium hypochlorite laundry bleach for industrial and institutional laundries. It whitens and brightens textiles and is dosed into the wash water through dilution and dispensing systems.

BENEFITS

- Highly concentrated, for industrial and institutional use
- Suitable for dilution and dispensing systems
- Keeps whites whiter and brighter



USES

Where to use

- Hospitals and care centers
- Hotels and motels
- Institutional laundries

What to clean

White washable textiles, in the wash of industrial and institutional laundries.

DIRECTIONS

1. For industrial and institutional laundries only: dose into the wash water through the laundry dilution and dispensing system.
2. Set the dose with your Gascó service technician.
3. Do not premix with other chemicals; in the wash, combine only with water and laundry detergent.
4. Never mix with acids (including laundry sours), ammonia or products that contain them: toxic gases are released.
5. Do not use the product full strength for cleaning surfaces.

AVAILABLE PACKAGES

Code	Package	UPC
D11062	Pail, 5 US gal (18.93 L)	787302110629
D11063	Drum, 55 US gal (208.2 L)	787302110636

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid	**Color**	Clear, yellow
Odor	Chlorine-like	**pH**	12 to 13
Relative density (water = 1)	1.15 to 1.20	**Flash point**	Not applicable (does not burn)
Flammability	Not flammable	**Solubility in water**	Completely miscible

SAFETY

DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.



Hazard ratings



Health	3
Flammability	0
Physical hazard	0

NFPA 704 and HMIS ratings: 0 minimal, 1 slight, 2 moderate, 3 serious, 4 severe.

Personal protection	**Eyes and face:** Chemical splash goggles. Add a face shield when pouring or transferring the undiluted product. **Hands:** Chemical-resistant gloves, such as nitrile rubber, neoprene, butyl rubber or PVC, when handling the undiluted product and, as the product label directs, for prolonged use. Confirm breakthrough time with the glove manufacturer for the conditions of use.
Storage	Store upright in the original, closed container in a cool, dry, well-ventilated area, away from direct sunlight and heat; the product loses strength faster at higher temperatures and in light. Store locked up and out of the reach of children. Keep away from acids, ammonia and ammonium compounds, reducing agents, organic materials and the other incompatible materials listed in SDS Section 10. Use corrosion-resistant containers and equipment, such as high-density polyethylene; do not use aluminum, copper, brass, zinc or unprotected steel.
Emergency	Poison Control: 1-800-222-1222 (24 hours)

Make sure your employees read and understand the Safety Data Sheet (SDS) and the product label before use. Safety values on this sheet are taken from SDS-D11062-D11063 version 1 (2026-10-25). SDSs in English and Spanish are available at www.gascoindustrial.com, from your sales representative or at (787) 737-4000.

Gascó Industrial Corp.
PO Box 1360, Gurabo, PR 00778
(787) 737-4000 · orders@gascoindustrial.com · www.gascoindustrial.com

For more information call (787) 737-4000 or visit www.gascoindustrial.com.