Sodium Hypochlorite 12%

Industrial sodium hypochlorite bleach for bleaching, cleaning, deodorizing and stain removal. It is always used diluted with water, for laundry, floors and stains.

BENEFITS

- Concentrated industrial bleach, used diluted with water
- Bleaches, cleans and deodorizes
- Removes stains
- For industrial, institutional and professional use

USES

Where to use

- Industrial and institutional facilities
- Laundries

What to clean

Laundry, floors and stains, always diluted with water.

DIRECTIONS

1. Always dilute with water strictly as the product label directs. Do not use the product full strength for cleaning surfaces.
2. Laundry: dose through the washer dispenser into the bleach step, at 2 to 10 fl oz per 100 lb of dry linen.
3. Mix only with water, and with detergent only where the product label says so.
4. Never mix with acids, ammonia, toilet bowl cleaners, rust removers or other cleaning products: toxic gases are released.
5. Use corrosion-resistant equipment, such as high-density polyethylene. Do not use aluminum, copper, brass, zinc or unprotected steel.

Dilution: Laundry: 2 to 10 fl oz per 100 lb of dry linen, by soil level, in water below 68 °C (155 °F). White and colorfast fabrics only.

AVAILABLE PACKAGES

Code	Package	UPC
D10056	Drum, 55 US gal (208.2 L)	787302100569

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid	**Color**	Clear, yellow
Odor	Chlorine-like	**pH**	12 to 13
Relative density (water = 1)	1.15 to 1.20	**Flash point**	Not applicable (does not burn)
Flammability	Not flammable	**Solubility in water**	Completely miscible

SAFETY

DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.



Hazard ratings



Health	3
Flammability	0
Physical hazard	0

NFPA 704 and HMIS ratings: 0 minimal, 1 slight, 2 moderate, 3 serious, 4 severe.

Personal protection	**Eyes and face:** Chemical splash goggles. Add a face shield when pouring or transferring the undiluted product. **Hands:** Chemical-resistant gloves, such as nitrile rubber, neoprene, butyl rubber or PVC, when handling the undiluted product and, as the product label directs, for prolonged use. Confirm breakthrough time with the glove manufacturer for the conditions of use.
Storage	Store upright in the original, closed container in a cool, dry, well-ventilated area, away from direct sunlight and heat; the product loses strength faster at higher temperatures and in light. Store locked up and out of the reach of children. Keep away from acids, ammonia and ammonium compounds, reducing agents, organic materials and the other incompatible materials listed in SDS Section 10. Use corrosion-resistant containers and equipment, such as high-density polyethylene; do not use aluminum, copper, brass, zinc or unprotected steel.
Emergency	Poison Control: 1-800-222-1222 (24 hours)

Make sure your employees read and understand the Safety Data Sheet (SDS) and the product label before use. Safety values on this sheet are taken from SDS-D10056 version 8 (2026-10-25). SDSs in English and Spanish are available at www.gascoindustrial.com, from your sales representative or at (787) 737-4000.

Gascó Industrial Corp.
PO Box 1360, Gurabo, PR 00778
(787) 737-4000 · orders@gascoindustrial.com · www.gascoindustrial.com

For more information call (787) 737-4000 or visit www.gascoindustrial.com.